



## TECHNICAL INFORMATION



name	layout dimensions (mm)			consumption pcs/m <sup>2</sup> at joints between faces 13.8 cm	quantity (pcs)		weight (kg)			max. tonnage up to 24 tonnes	
	height	length	width		layer	pallet	pcs	pallet	including pallet	number of pallets	pcs
<b>BEST LARGO</b>	170/190	330	260/310	13.13	9	27	17	459	489	24	648

We are holders of the Gold Certificate for complete certification according to ISO 9001, ISO 14001, ISO 50001, ISO 45001. Our products are manufactured and inspected pursuant to European harmonized standards.

production standard	maximum deviation from declared production dimensions		tensile strength	frost resistance ČSN EN 13 198, Annex A
	width and length	height		
PN-BEST-8-2009/A	±5 mm	±5 mm	≥ 15 MPa	50 cycles

## EXPLANATIONS OF PICTOGRAMS



Surface  
interstitial

## SURFACE FINISHES AND COLOURS



NATURAL



CAMEL

surface	characteristics	colour
INTERSTITIAL	surface with interstitial structure	natural, caramel

## GENERAL INFORMATION

Fittings made of plain vibro-pressed concrete with an interstitial structure. The blocks are designed for slope stabilization. The minimum shipping quantity is 1 piece. The goods are loaded on marked pallets BEST (30 kg) or BEST large (38 kg) according to the production capacity of individual plants.

During installation, it is important to follow the correct procedure according to the instructions for use ([www.best.cz](http://www.best.cz)).

Note: BEST LARGO is a slope element in which no plastic bottom is inserted.



**TECHNICAL DRAWINGS (mm)**

