


## TECHNICAL INFORMATION



Layout dimensions

name		layout dimensions (mm)			consumption (pcs/lm)	quantity (pcs)		weight (kg)			max. tonnage up to 24 tonnes	
		height	length	width		layer	pallet	pcs	pallet	pallet included	number of pallets	m <sup>2</sup>
BEST SINIA I		250	1000	100	1	8	24	54.5	1308	1338	17	408
BEST SINIA II		200	1000	100	1	8	24	47	1128	1158	20	480

We are holders of the Gold Certificate for complete certification according to ISO 9001, ISO 14001, ISO 50001, ISO 45001. Our products are manufactured and inspected pursuant to European harmonized standards.

product height	product width	production standard	maximum deviation from declared production dimensions		bending tensile strength	skid/slip resistance	ČSN 73 1326, weather resistance, method A
			width and height	length			
200 mm 250 mm	100 mm	ČSN EN 1340	±3 % (min. 3 mm, max. 5 mm)	max. ±%	≥ 3.5 MPa	satisfactory	≤ 1.0 kg/m <sup>2</sup> after 100 cycles

### EXPLANATIONS OF PICTOGRAMS




The park curb for areas with low traffic intensity, parking spaces of family houses, non-motorized roads, parking areas



Surface basic

## SURFACE FINISHES AND COLOURS



NATURAL

surface	characteristics	colour
STANDARD	standard surface with natural aggregate roughness corresponding to the visible layer of concrete paving	natural

## GENERAL INFORMATION

Two-layer vibrated curb with high strength, frost resistance, surface resistance to water and chemical de-icing agents. The curb has low abrasion and good adhesion properties. BEST concrete elements are permanently impregnated against contamination.

The minimum shipping quantity is 1 piece. The goods are loaded on marked pallets BEST (30 kg) or BEST large (38 kg) according to the production capacity of individual plants.

When laying, the pieces are to be joined together, following the correct procedure according to the instructions for use ([www.best.cz](http://www.best.cz)).



703/2020

