




TECHNICAL INFORMATION



name	layout dimensions (mm)			consumption of the "binder-stretcher"		quantity (pcs)		weight (kg)			max. tonnage up to 24 tonnes	
	height	length	width	pcs/m ²	pcs/lm	layer	pallet	pcs	pallet	including pallet	number of pallets	pcs
BEST VARIO	300	570	385/236	8.26	2.48	4	12	50	600	630	24	288

We are holders of the Gold Certificate for complete certification according to ISO 9001, ISO 14001, ISO 50001, ISO 45001. Our products are manufactured and inspected pursuant to European harmonized standards.

production standard	maximum deviation from declared production dimensions		tensile strength	Frost resistance ČSN EN 13 198, Annex A
	width and length	height		
PN-BEST-08-2009/A	±5 mm	±5 mm	≥ 15 MPa	50 cycles

EXPLANATIONS OF PICTOGRAMS



Surface interstitial

SURFACE FINISHES AND COLOURS



NATURAL



CAMEL

surface	characteristics	colour
INTERSTITIAL	surface with interstitial structure	natural, caramel

GENERAL INFORMATION


Universal masonry fittings made of plain vibro-pressed concrete with an interstitial structure. The blocks are intended for the construction of walls.

The minimum shipping quantity is 1 piece. The goods are loaded on marked pallets BEST (30 kg) or BEST large (38 kg) according to the production capacity of individual plants.

During installation, it is important to follow the correct procedure according to the instructions for use (www.best.cz).

Note: You can use plastic bottoms (available at www.best.cz) to fill the individual elements of BEST VARIO.

There are 2 bottoms for 1 BEST VARIO element.



fitting of plastic bottoms

TECHNICAL DRAWINGS (mm)

